



Agfa :SherpaProof System

SWOP® Application Data Sheet

The SWOP® Review Committee has approved the use of off-press proofs as input material to publications. SWOP Specifications recommend that “the appearance of an off-press proof must closely simulate a SWOP press proof”.

1. Manufacturer:

Agfa-Gevaert NV.
Septestraat 27
B2640 Mortsel
++32.3.444.21.11 Phone
++32.3.444.70.94 Fax
WWW.agfa.com
color_support@europe.agfa.com



Certified - November 2005

2. Product:

Agfa :SherpaProof system

3. Introduction:

The Agfa :SherpaProof family of inkjet digital proofing systems produce color proofs for use in SWOP® applications by using ICC profiles created with ColorTune Pro color management software. Agfa :Sherpa Digital Proofing systems utilize ApogeeX Rip and workflow software, QmsX software and a spectrophotometer for engine calibration and Proofer-Check consistency. The Agfa :Sherpa Digital Proofing systems can be color calibrated to match other proofing systems, and a broad range of printing conditions. In addition to matching the CMYK color space of the target condition, the Agfa :Sherpa Digital Proofing Systems uses PANTONE® and user defined libraries for spot color rendering.

4. Control Guide:

SWOP® specifies that a control guide such as a SWOP Proofing Bar be supplied on every off-press proof. As a minimum, this guide should contain solids of the primary process colors and two-color overprints, as well as 25%, 50% and 75% tint in 133-line screen ruling of each of the process colors. Any color bar should be checked for accuracy of the original values. This can be performed by using the Proof to Reference check through :QmsX and/or :Sherpa CMS.

Agfa recommends that the following control guide(s) be used in producing :Sherpa Digital Color Proofs. Control Guide SWOP Digital Proofing Color Bar and/or the Digital Proof Comparator when producing :SherpaProofs. The use and interpretation of the control bars is the responsibility of the user.

5. System components & Procedure

The following components and limited processing procedures shall be used with the Agfa :Sherpa Digital Color Proofing System in order to achieve conformance with this Application Data Sheet:

- Agfa :ApogeeX Proofer or any :ApogeeX configuration with integrated Proofing option v2.5 (SP2) or later
- Epson Stylus Pro™ 4800/7800 or 9800
- Agfa :QmsX v 2.5 (+SP2) or later
- Agfa :Sherpa CMS v 1.2 or later
- Agfa :ColorTune Pro v 4.2 update 1 or later
- X-Rite DTP41, DTP45, 530 or GretagMacbeth SpectroLino/SpectroScan
- :AgfaJet Microporous Digital Proofing base (AMDP)
- Agfa/Epson Ultrachrome K3 Ink™ (8 inks)

Procedure for making proofs for use in SWOP® applications with the Agfa :Sherpa Proofing System”:

- Load the appropriate :AgfaJet Microporous Digital Proof base on the Epson Stylus Pro™ 4800/7800/9800 Use Agfa/Epson UltraChrome K3 ink™ (8 inks)
- Calibrate the Epson Stylus Pro™ Engine with QmsX as outlined in the :QmsX user documentation.
- Perform a “proofer check” calibration check as outlined in the :QmsX user documentation.
- If Calibration is good :QmsX will indicate that a “confidence score” of higher than 97.5% is reached.
- In :ApogeeX generate a Jobticket in which the following ICC profiles are enabled for the proofing flow: (for detailed procedure follow outlines in :ApogeeX Help)
 - for the press-profile: SWOP-textweb-AgfaCT-D50.icm
 - for the Proofer-profile: PP_EpsK3_720_UHQ_swop.icc

6. Finishing Procedure

The following finishing instructions are necessary in order that the Agfa :SherpaProof™ Digital Proofing System conforms to this Application sheet. Allow proofs to dry for approximately 30 minutes prior to making critical color judgments

7. Finished Proof Characteristics

When properly processed and/or produced, the following are the characteristics to be expected from Agfa :Sherpa™ Digital Proofs. All of the below readings were made with a properly calibrated X-Rite® 530 spectrophotometer. Density readings were made absolute. As with any brand of Spectrophotometer – small variations in readings are to be expected from model to model and site to site, proper instrument calibration helps to minimize the differences.

Substrate/background Densities (paper color simulated): Status T spectral products used (absolute)

Cyan (red Filter):	0.10	L* = 89.7
Magenta (green filter):	0.13	a* = 1.4
Yellow (blue filter):	0.16	b* = 5.3
Black (visual filter):	0.12	C* = 5.5
		H(ab)* = 74

	Density 50%	TVI at 50%	Print Contrast At 75%	Color (per CGATS .5)					
				L*	a*	b*	C*	h(ab)*	ΔE ₉₄
Tolerance	± 0.05	± 3.0	±5.0						-
Yellow	1.00	15	29	85.3	-3.4	85.7	84.2	92.2	4
Magenta	1.66	22	37	47.3	72.7	0.3	72.5	0.1	4
Cyan	1.36	19	35	54.8	-37.4	-42.5	56.2	228.2	4
Black	1.76	18	36	12.4	2.4	5.2	7.2	66.5	4
Red				47.7	67.3	45.2	82.3	34.6	4
Green				50.4	-61.3	26.1	69.6	156.1	4
Blue				24.2	19.4	-40.1	46.2	296.5	4
Tolerance	Cyan	Magenta	Yellow	L*	a*	b*	C*	h(ab)*	ΔE ₉₄
± 0.05									
3 Color	0.36	0.36	0.38	71.3	0.2	1.5	1.7	81.3	4
Gray 25 %									
3 Color	0.63	0.65	0.67	54.5	0.8	2.4	2.3	70.6	4
Gray 50 %									
3 Color	0.97	0.95	0.99	39.3	-1.5	2.6	3.0	120.1	4
Gray 75 %									

Density is the major filter value and TVI is computed using the Murray-Davies equation.

8. Sample Proof

Agfa-Gevaert NV. has supplied two sets of Agfa :SherpaProof™ Digital Proofs which conform to this Application Data sheet to SWOP® for analysis and retention.

All registered trademarks are the property of their respective owners