

SWOP® Off-Press Proof Application Data Sheet

Matchprint Virtual Proofing System – LCD with Eizo ColorEdge CG21 Display

The SWOP Review Committee has approved the use of off-press proofs as input material to publications. SWOP specifications recommend that: "The appearance of an off-press proof used in this application must closely simulate a SWOP Certified Press Proof." See other explanations and recommendations as outlined on pages 21 and 47 of the 2001 edition of the SWOP specifications.

I. Manufacturer

Kodak Polychrome Graphics
401 Merritt 7, 3rd Floor
Norwalk, CT 06851



Certified – September, 2004

II. Product

Matchprint Virtual Proofing System – LCD with Eizo ColorEdge CG21 Display

III. Introduction

Kodak Polychrome Graphics (KPG) Matchprint Virtual Proofing System – LCD provides for color-accurate viewing of CMYK files on RGB electronic monitors. Users may select custom or standard color rendition targets, including a standard / supplied color profile based on data contained in ANSI CGATS TR001 as suggested by SWOP. This Matchprint Virtual Proof color profile is freely available to all users. Visual match is apparent by selecting this profile when viewing a digital file on the monitor screen and simultaneously viewing an actual SWOP Certified Press Sheet. Matchprint Virtual Proof – LCD includes a software tool to automatically confirm compliance with color measurement data in this SWOP Off-Press Proof Application Data Sheet.

IV. Control Guide

SWOP Specifications recommend the use of the GATF / SWOP Digital Color Bar or other suitable guides which meet these requirements. Each Matchprint Virtual Proofing System incorporates an automatic process to calibrate the system and its monitor on a daily basis. Users can confirm color rendition according to SWOP standards by selecting the "information" button (see *Matchprint Virtual Proofing System – LCD Operator Reference*) when viewing an image file.

V. System Components

Hardware:

1. Eizo Nanao Technologies ColorEdge CG21 LCD Display
2. KPG Monitor Calibrator, a specially calibrated and certified colorimeter supplied by KPG for use with the Matchprint Virtual Proofing System - LCD.

Software:

1. Macintosh OS/X Version 10.3 Operating System software
2. KPG Matchprint Virtual Proofing Monitor Software – a supplied component of the Matchprint Virtual Proofing System – LCD.

Environment and Viewing:

Subdued ambient light is recommended for optimum color viewing. While LCD displays offer a number of advantages compared to conventional CRT displays, viewing angle for critical color judgment is more restrictive. KPG recommends viewing the LCD display from a position directly in front and perpendicular to the center of the LCD screen. KPG recommends the companion model CH1-A hood for the Eizo ColorEdge CG21 display.

Setup and Protocol:

Follow these steps to ensure Matchprint Virtual Proof viewing in conformance with SWOP requirements:

1. Switch on all system components and allow one hour warm-up. The Matchprint Virtual Proof – LCD system automatically enforces this one-hour warm-up from a cold start.
2. Ensure the Matchprint Virtual Proof – LCD system is calibrated. If you are unsure, launch the MVP System Check applet from the Matchprint Virtual Folder in the Dock area to obtain a readiness report.
3. Launch the MVP Color Check application from either the Matchprint Virtual folder in the Dock area or from Macintosh HD | Applications | Matchprint Virtual | Modules | Color Check.
4. When the MVP Colorimeter dialog box appears, confirm the KPG Monitor Calibrator is placed flat on an opaque surface and click Continue. When the colorimeter dark calibration is complete (approximately 10 seconds), click on the LCD display screen to select it for SWOP color confirmation.
5. Position the KPG Monitor Calibrator flat against the display within the on-screen outline and press any key.
6. In the Measurement dialog box, click on the Color Check button. A Choose File dialog box appears.
7. Select Choose, then select the file with the LCD monitor type and "AutoSWOPADS" in the name and click Open. Click Continue in the Color Check dialog box. Re-confirm placement of the KPG Monitor Calibrator and press any key.
8. A series of color patches automatically appears successively on-screen, corresponding to the colors in this SWOP Application Data Sheet.
9. When automatic color measurement is complete, a data table is presented on screen. Within this table are actual color measurement values and Delta E comparisons with values for each color in this SWOP ADS. The table can be printed using File | Print.
10. To independently confirm Matchprint Virtual Proof viewing in compliance with SWOP standards, open a proof view (see *Matchprint Virtual Proof – LCD Operator Reference* for instructions) and click on the "information tool" ("i" shaped icon). The resulting window should indicate:

Color Profile

CMYK Printing Process	Standards
Proofing Condition	US Web SWOP

If this is not the case, close the information window, close the image window and return to the window showing the image thumbnail. Select "Properties" in the column to the right of the thumbnail image. In the resulting window, utilize the selection boxes to ensure the above noted two settings are selected. Click on "Process Again" and close the window.

See the *Matchprint Virtual Proof – LCD Operator Reference* and *Administrator Reference* for explanations of these and other tools.

V. Finishing Procedures

No finishing procedures are necessary with the Matchprint Virtual Proofing System - LCD.

VI. Finished Proof Characteristics

A properly made proof using the Matchprint Virtual Proofing System – LCD with Eizo ColorEdge CG21 Display should have the following color characteristics:

Color	Absolute Density	L*	C*	h _{ab}
Cyan	100	55.9	48.8	236.1
Cyan	75	63.5	38.5	234.5
Cyan	50	71.2	25.7	232.8
Magenta	100	45.6	67.2	358.0
Magenta	75	53.4	55.3	356.3
Magenta	50	64.3	37.0	355.8
Yellow	100	87.2	86.0	97.3
Yellow	75	85.7	72.0	99.7
Yellow	50	86.8	50.1	101.2
Black	100	20.1	--	--
Black	75	38.7	--	--
Black	50	55.6	--	--
Red	100	43.8	81.7	37.5
Green	100	52.7	67.2	151.1
Blue	100	23.1	52.3	303.1
Paper	--	89.4	4.2	88.6

All measurements are made with the supplied KPG Monitor Calibrator and MVP Color Check software application.

Aggregate measured color of any patch should be within 2.5 delta E of the above values.

VII. Sample Proofs

Sample Matchprint Virtual Proofing System proofs conforming to this Application Data Sheet have been demonstrated to the SWOP Technical Committee for their inspection and verification.

CALL TOLL-FREE **1-877-KPGraphics** (1-877-574-7274) FOR ADDITIONAL INFORMATION
OR VISIT US ON THE WEB AT www.kpgraphics.com

© 2004 Kodak Polychrome Graphics. All rights reserved. Matchprint is a trademark of Kodak Polychrome Graphics. Kodak is a trademark of Eastman Kodak Company. All trademarks and registered trademarks used herein are the property of their respective owners.

Kodak Polychrome
G R A P H I C S

ADS 0028-041006